



Technical data sheet

Stainless Steel Filter Regulator  
Compressed Air(MSS-FR)



Technical Data:	Operating Parameters	
	Inlet Pressure	7-426PSI
	Outlet Pressure	7-426PSI
	Design Proof Pressure	850PSI
	Flow Capacity:	1/4 2200 L/min (MSS-FR-04) 3/8 2500 L/min (MSS-FR-06) 1/2 3800 L/min (MSS-FR-08)
	Filter Bowl Capacity	110cc
	Operating Temperature	-10C-70C
	Filtration	5micron
	Connection Thread	NPT
	Standard Drain	Auto
	Weight	2000g
	Regulator construction	Piston



**Technical data sheet**      **Stainless Steel Filter Regulator  
 Compressed Air(MSS-FR)**

<b>Media Contact Materials:</b>	Body	316 Stainless Steel
	Bowl	316 Stainless Steel
	Filter Element	316 Stainless steel
	Pressure gauge	Case 304 Stainless Steel
	Connection	316 Stainless Steel

<b>Included Accessories</b>	Mounting Bracket	Hex Head Screws x2
	Pressure gauge	Plug

<b>Features and Benefits:</b>	• For high pressure use
	• Corrosion and chemical resistance
	• Accurate and sensitive pressure setting

**Drawing:**

